



ECODAS Product Line

Clean Technology and Forward-looking Engineering



Data	T100	T150	T300	T1000	T2000
Dimensions (L x W x H)	200 x 115 x 212 cm 6.6 x 3.8 x 7.0 ft.	195 x 250 x 300 cm 6.4 x 8.2 x 9.9 ft.	220 x 260 x 330 cm 7.2 x 8.5 x 10.8 ft.	510 x 460 x 640 cm 16.7 x 15.1 x 21 ft.	510 x 460 x 640 cm 16.7 x 15.1 x 21 ft.
Average Cycle Time Load to Load	30 Minutes	30 Minutes	30 Minutes	35 Minutes	45 Minutes
Volume Capacity	100 liters / 26.4 gal	150 liters / 39.6 gal	350 liters / 92.5 gal	1100 liters / 290.6 gal	2500 liters / 660.4 gal
Average Process Weight Capacity	22 – 33 lb. / cycle 10 – 15 kg / cycle	33 – 51 lb. / cycle 15 – 23 kg / cycle	77 – 115 lb. / cycle 35 – 52 kg / cycle	242 – 364 lb. / cycle 110 – 165 kg / cycle	550 – 825 lb. / cycle 250 – 375 kg / cycle
Number of Shifts	Average Daily Machine Capacity (lb. & kg)				
1 Shift 8 hrs./day	440 lb. 200 kg	672 lb. 304 kg	1,536 lb. 696 kg	4,155 lb. 1,886 kg	7,333 lb. 3,333 kg
2 Shifts 16 hrs./day	880 lb. 400 kg	1,344 lb. 608 kg	3,072 lb. 1,392 kg	8,311 lb. 3,771 kg	14,667 lb. 6,667 kg
3 Shifts 24 hrs./day	1,320 lb. 600 kg	2,016 lb. 912 kg	4,608 lb. 2,088 kg	12,466 lb. 5,657 kg	22,000 lb. 10,000 kg

Profil
 Medical Waste
 Methods
 Technology
 Compliance
 Advantages
 Offerings